

**IN THE CLAIMS:**

Please amend claims 1, 3, 9, 10, 13-17, 21-26, and 29-32 as follows.

1. (Currently Amended) A method, comprising:

establishing a communication session between a user equipment associated with a first access network and a node of a communication system via a second network and at least one entity of said communication system between said user equipment and said node;

putting the session on hold;

reserving resources for said session while said session is on hold; and

resuming said session with a message from said user equipment by which ~~an access network~~ a charging identifier for the first access network is distributed within the second network, wherein the first access network is different from the second network.

2. (Previously Presented) The method as claimed in claim 1, further comprising:

determining if charging information is provided during the establishment of said session and carrying out the putting of the session on hold to the resuming of said session only when it has been determined that the charging information has not been provided.

3. (Currently Amended) A method, comprising:

modifying an existing communication session between user equipment associated with a first access network and a node of a communication system via a second network and at least one entity of said communication system between said user equipment and said node;

putting the session on hold;

reserving resources for the modified session while said session is on hold; and

resuming said session with a message from said user equipment by which ~~an a~~  
~~access network~~ charging identifier for the first access network is distributed within the second network, wherein the first access network is different from the second network.

4. (Previously Presented) The method as claimed in claim 3, further comprising:

determining if charging information is provided during the modifying of said session and carrying out the putting of the session on hold to the resuming of said session only when it has been determined that the charging information has not been provided.

5. (Previously Presented) The method as claimed in claim 1, wherein the establishing of said session comprises using session initiation protocol for said session.

6. (Previously Presented) The method as claimed in claim 1, wherein the establishing of said session comprises operating at least part of said communication system in accordance with universal mobile telecommunications system standard.

7. (Canceled)

8. (Previously Presented) The method as claimed in claim 1, further comprising:

configuring said charging identifier to comprise at least a general packet radio service charging identifier.

9. (Currently Amended) The method as claimed claim 1, wherein the distributing of the ~~access-network~~ charging identifier for the first access network comprises distributing the ~~access-network~~ charging identifier for the first access network provided in a charging vector.

10. (Currently Amended) The method as claimed in claim 9, wherein the distributing of the ~~access-network~~ charging identifier for the first access network comprises distributing the charging identifier for the first access network in a charging vector, wherein said charging vector comprises a p-charging vector.

11. (Previously Presented) The method as claimed in claim 1, wherein the establishing of the session comprises establishing a session wherein said at least one entity comprises a gateway general packet radio service support node.

12. (Previously Presented) The method as claimed in claim 1, wherein the establishing of said session comprises establishing a session wherein said at least one entity comprises a proxy call session control function.

13. (Currently Amended) The method as claimed in claim 1, wherein the establishing of said session comprises establishing a session wherein said at least one entity comprises a policy decision function~~-function~~.

14. (Currently Amended) A method as claimed in claim 11, wherein the establishing of said session comprises establishing a session wherein said at least one entity comprises a proxy call session control function, the method further comprising sending the charging identifier for the first access network from the gateway general packet radio service node to the proxy call session control function.

15. (Currently Amended) The method as claimed in claim 11, wherein the establishing of said session comprises establishing a session wherein said at least one entity comprises a policy decision function , the method further comprising sending the

charging identifier for the first access network from the gateway general packet radio service node to the policy decision function.

16. (Currently Amended) The method as claimed in claim 14, wherein the establishing of said session comprises establishing a session wherein said charging identifier for the first access network is sent from the gateway general radio packet service node to the proxy call session control function in a common open policy service message.

17. (Currently Amended) The method as claimed in claim 15, wherein the establishing of said session comprises establishing a session wherein said charging identifier for the first access network is sent from the gateway general radio packet service node to the policy decision function in a common open policy service message.

18. (Previously Presented) The method as claimed in claim 1, wherein the establishing of said session comprises establishing a session wherein said node comprises a user agent server.

19. (Previously Presented) The method claim as claimed in claim 5, wherein the establishing of said session comprises establishing a session wherein said charging identifier is sent in an invite message.

20. (Previously Presented) The method as claimed in claim 1, wherein the establishing of said session comprises establishing a session wherein said node comprises user equipment.

21. (Currently Amended) A communication system, said system comprising:  
a user equipment associated with a first access network, wherein the communication system is configured to support a communication session of said user equipment; and

at least one entity between said user equipment and a node with which the user equipment is configured to establish a session via a second network,

wherein the system is configured to establish said session between the user equipment and the node via said at least one entity, at least one of said node and said user equipment is configured to put the session on hold, at least one of said node and said user equipment is configured to reserve resources for said session while said session is on hold, at least one of said node and said user equipment is configured to resume said session with a message from said user equipment by which at least one entity distributes ~~an access network~~ a charging identifier for the first access network within the second network, and

wherein the first access network is different from the second network.

22. (Currently Amended) A communication system, said system comprising:

a user equipment associated with a first access network, wherein the communication system is configured to support a communication session of said user equipment; and

at least one entity between said user equipment and a node with which the user equipment is configured to establish a session via a second network, wherein the system is configured to modify a session between the user equipment and the node via said at least one entity, at least one of said node and said user equipment is configured to put the session on hold, at least one of said node and said user equipment is configured to reserving resources for said modified session while said session is on hold, at least one of said node and said user equipment is configured to resume said session with a message from said user equipment by which at least one entity distributes ~~an access network~~a charging identifier for the first access network within the second network, and

wherein the first access network is different from the second network.

23. (Currently Amended) A communication system, the system comprising:

at least one entity means between user equipment associated with a first access network and a node with which the user equipment is configured to establish a session via a second network;

establishing means for establishing said session between the user equipment and the node via said at least one entity means;

placement means for putting the session on hold;

reserving means for reserving resources for said session while said session is on hold; and

resuming means for resuming said session with a message from said user equipment by which ~~an access network~~ a charging identifier for the first access network is distributed within said second network, wherein the first access network is different from the second network.

24. (Currently Amended) A communication system, the system comprising:

at least one entity means between user equipment associated with a first access network and a node with which the user equipment is configured to establish a session via a second network;

modifying means for modifying an existing session between the user equipment and the node via said at least one entity;

placement means for putting the session on hold;

first reserving means for reserving resources for the modified session while said session is on hold;

second reserving means for reserving resources for the modified session while said session is on hold; and

resuming means for resuming said session with a message from said user equipment by which ~~an access network~~ a charging identifier for the first access network is

distributed within said second network, wherein the first access network is different from the second network.

25. (Currently Amended) A network apparatus, comprising:

a network element configured to establish a communication session with a node via a first access network and a second network, wherein said network element is further configured to put said session on hold, to reserve resources for said session while said session is on hold, and to resume said session with a message from said user equipment by which ~~an access network~~a charging identifier for the first access network is distributed within the second network, and wherein the first access network is different from the second network.

26. (Currently Amended) A network apparatus, comprising:

a network element configured to modify a communication session with a node via a first access network and a second network, wherein said network element is further configured to put the session on hold, to reserve resources for modifying said session while said session is on hold, and to resume said session with a message from said user equipment by which ~~an access network~~a charging identifier for the first access network is distributed within said second network, and wherein the first access network is different from the second network.

27. (Previously Presented) A network apparatus according to claim 25, wherein the network element is a user equipment.

28. (Previously Presented) A network apparatus according to claim 26, wherein the network element is a user equipment.

29. (Currently Amended) A computer program embodied on a computer readable medium for supporting a communication session of user equipment associated with a first access network, wherein said communication system comprises at least one entity between said user equipment and a node with which the user equipment is configured to establish a session via a second network, the computer program being configured to perform:

establishing said session between the user equipment and the node via said at least one entity;

putting the session on hold;

reserving resources for the modified session while said session is on hold; and

resuming said session with a message from said user equipment by which ~~an access network~~ a charging identifier for the first access network is distributed within the second network, wherein the first access network is different from the second network.

30. (Currently Amended) A computer program embodied on a computer readable medium for supporting a communication session of user equipment associated with a first access network, wherein said communication system comprises at least one entity between said user equipment and a node with which the user equipment is configured to establish a session via a second network, the computer program being configured to perform:

modifying an existing session between the user equipment and the node via said at least one entity;

putting the session on hold;

reserving resources for the modified session while said session is on hold; and

resuming said session with a message from said user equipment by which ~~an access network~~ a charging identifier for the first access network is distributed within the second network, wherein the first access network is different from the second network.

31. (Currently Amended) A network element for establishing a communication session with a node via a first access network and a second network, said network element comprising:

means for putting said session on hold;

means for reserving resources for said session while said session is on hold; and

means for resuming said session with a message from said user equipment by which ~~an access network~~ a charging identifier for the first access network is distributed

within the second network, wherein the first access network is different from the second network.

32. (Currently Amended) A network element for modifying a communication session with a node via a first access network and a second network, said network element comprising:

means for putting the session on hold;

means for reserving resources for modifying said session while said session is on hold; and

means for resuming said session with a message from said user equipment by which ~~an access network~~a charging identifier for the first access network is distributed within said second network, wherein the first access network is different from the second network.